




# HMSA BEARING MANUFACTURING LIMITED



7321 BECBM Bearing 2D drawings and 3D CAD models

105 mm x 225 mm x 49 mm skf 7321 BECBM  
Single row angular contact ball bearings

Bearing No. 7321 BECBM

Size	225x105x49 mm
Bore Diameter	225 mm
Outer Diameter	105 mm
Width	49 mm
d	105 mm
D	225 mm
B	49 mm
d <sub>1</sub>	151.65 mm
d <sub>2</sub>	127.87 mm
D <sub>1</sub>	181.35 mm
a	94 mm
r <sub>1,2</sub> - min.	3 mm
r <sub>3,4</sub> - min.	1.1 mm
d <sub>a</sub> - min.	119 mm
D <sub>a</sub> - max.	211 mm
D <sub>b</sub> - max.	218 mm
r <sub>a</sub> - max.	2.5 mm
r <sub>b</sub> - max.	1 mm
Basic dynamic load rating - C	216 kN
Basic static load rating - C <sub>0</sub>	208 kN
Fatigue load limit - P <sub>u</sub>	7 kN
Reference speed	3800 r/min
Limiting speed	3800 r/min
Calculation factor - k <sub>r</sub>	0.1



## HMSA BEARING MANUFACTURING LIMITED

Calculation factor - $k_a$	1.6
Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - $Y_0$	0.52
Calculation factor - $Y_1$	0.55
Calculation factor - $Y_2$	0.93
Calculation factor - X	0.35
Calculation factor - $Y_0$	0.26
Calculation factor - $Y_1$	
Calculation factor - $Y_2$	0.57
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	9.12
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3   ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	105MM Bore; 225MM



# HMSA BEARING MANUFACTURING LIMITED

	Outside Diameter; 49MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3   ISO P6; No Filling Slot; No Snap Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	7321 BECBM
Weight / LBS	20.097
Bore	4.134 Inch   105 Millimeter
Width	1.929 Inch   49 Millimeter
Outside Diameter	8.858 Inch   225 Millimeter
bore diameter:	105 mm
radial static load capacity:	208 kN
outside diameter:	225 mm
cage material:	Brass
overall width:	49 mm
outer ring width:	49 mm
contact angle:	40 °
maximum rpm:	3800 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	2.5 mm



## HMSA BEARING MANUFACTURING LIMITED

radial dynamic load capacity:	216 kN
series:	73
$d_1$	151.65 mm
$d_2$	127.87 mm
$D_1$	181.35 mm
$r_{1,2}$ min.	3 mm
$r_{3,4}$ min.	1.1 mm
$d_a$ min.	119 mm
$D_a$ max.	211 mm
$D_b$ max.	218 mm
$r_a$ max.	2.5 mm
$r_b$ max.	1 mm
Basic dynamic load rating C	216 kN
Basic static load rating $C_0$	208 kN
Fatigue load limit $P_u$	6.95 kN
Calculation factor A	0.669
Calculation factor $k_r$	0.1
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor $Y_0$	0.26
Calculation factor $Y_2$	0.57
Calculation factor X	0.57
Calculation factor $Y_0$	0.52
Calculation factor $Y_1$	0.55
Calculation factor $Y_2$	0.93
Mass bearing	8.55 kg